

## LINCAT SILVERLINK PROPANE GAS COUNTER-TOP CHARGRILL - W 600 MM - 17.6 KW

## **MODEL:** CG6/P



Create that distinctive chargrilled flavour and branded appearance without the need for messy lava rocks with the Silverlink 600 Gas Chargrill. Utilising innovative radiants instead, the chargrill experience is much cleaner, while the twin zones make for maximum flexibility. The variable heat control and heat retaining cooking grids produce the clean, sharp chargrilled marks that will make your dishes even more appetizing. It's perfect for cafes, bars and restaurants.

**SILVERLINK 600** 

#### PRODUCT OPTIONS AND ACCESSORIES

- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CN6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm
- SLS6 Lincat Silverlink 600 Free-standing Floor Stand for units W 600 mm

#### **PRODUCT FEATURES**

- Uses radiants which replaces the need for using messy lava rocks
- Twin zones for maximum flexibility
- The variable heat control and heat retaining cooking grids produce the clean, sharp chargrilled marks
- Splashguard to project surrounding surfaces from splashes
- Removable branding bars to allow for easy cleaning and access
- Drip drawer to collect all the cooking liquids to reduce cleaning times







## LINCAT SILVERLINK PROPANE GAS COUNTER-TOP CHARGRILL - W 600 MM - 17.6 KW

# MODEL: CG6/P

WEIGHTS & DIMENSIONS	
Width	600 mil
Depth	652 mil
Height	414 mil
Weight	35.3 kg

SHIPPING DETAILS	
Ship Width	70 cm
Ship Depth	70 cm
Ship Height	63.5 cm
Ship Weight	38.83 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

## **PRODUCT CERTIFICATIONS**



ENERGY SPECS	
Primary Energy Type	Gas
Electrical Kilowatts	17.6 kW
Electrical Plug Type	Not Applicable
Number of Electrical Plugs	Not Applicable
Electrical Connection Type	Not Applicable
Number of Electrical Conductor Wires	1

Gas Type	Propane
Gas Total BTUs	60051 BTU
Gas Inlet Size	0.5 in
Gas Inlet Pressure Required	20 mBar
Gas Consumption at Max Use Per Hour	1.26 m <sup>3</sup>
Total Heat Input at Max Use	14.5 kW, 49500 BTU per hour

Not Applicable
Stainless Steel
Countertop
Stainless Steel
Mechanical, Rotary Control Knob
440 mm
477 mm
91 x 115g [4oz] burgers [frozen] per hour

Grate Type	Cast Iron
Ignition Type	Pilot Light
Number of Burners	2
Number Of Controls	2
Radiant Material	Stainless Steel
Ventless Cooking Technology	No
Slide Out Warming Rack	No
Towel Bar	No

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 09, 2025







**MODEL: CG6/P** 


### **BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

## **TECHNICAL DRAWING**







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 09, 2025

