

LINCAT SILVERLINK PROPANE GAS COUNTER-TOP SALAMANDER GRILL - W 750 MM - 6.8 KW

MODEL: GR7/P



Sometimes during fast turnaround times, you need to be able to toast and grill at speed. The Silverlink 600 Gas Salamander Grill is ideal for these scenarios. Perfect for any modestly-sized, fast-paced restaurant, pub or takeaway, the grill boasts powerful ceramic plaque burners for rapid heat up, with four shelf positions to give maximum flexibility for all catering operations. The grill is also supplied with a double-sided alloy branding plate, which provides a branded appearance and distinctive taste, and a fat collection tray. Producing perfectly grilled meat, fish, and toast has never been as simple or stress-free.

SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- GR7/BS BENCH STAND FOR GR7
- BR39 BRANDER GR7
- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- GR7/WS WALL SHELF FOR GR7

PRODUCT FEATURES

- Powerful ceramic plaque burners for rapid heat up
- 4 shelf positions to give maximum flexibility for all catering operations
- Supplied with a double sided alloy branding plate and fat collection tray
- Cool touch handles for safety
- · Enamelled interior and hood for easy cleaning
- · Flame failure device for maximum safety







LINCAT SILVERLINK PROPANE GAS COUNTER-TOP SALAMANDER **GRILL - W 750 MM - 6.8 KW**

MODEL: GR7/P

WEIGHTS & DIMENSIONS	
Width	750 mil
Depth	423 mil
Height	405 mil
Weight	34.7 kg

SHIPPING DETAILS	
Ship Width	85.5 cm
Ship Depth	70 cm
Ship Height	49.5 cm
Ship Weight	38.17 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS	
Primary Energy Type	Gas
Electrical Kilowatts	6.8 kW
Electrical Plug Type	Not Applicable
Number of Electrical Plugs	Not Applicable
Electrical Connection Type	Not Applicable
Gas Type	Propane

Gas Total BTUs	23202 BTU
Gas Inlet Size	0.5 in
Gas Inlet Pressure Required	37 mBar
Gas Consumption at Max Use Per Hour	0.44 m^3
Total Heat Input at Max Use	6.8 kW, 22200 BTU per hour

ADDITIONAL SPECIFICATIONS	
Broiler Base Configuration	Not Applicable
Broiler Type	Salamander
Construction Materials	Stainless Steel
Control Type	Mechanical
Cooking Area Plate Depth	275 mm
Cooking Area Plate Width	580 mm

Food Production Rate	56 x 115g [4oz] burgers [frozen] per hour
Heat Location	Top Only
Heat Source Type	Ceramic
Number of Heating Zones	1
Number of Shelf Positions	4
Ventless Cooking Technology	No

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 09, 2025










MODEL: GR7/P

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 09, 2025

