

## LINCAT SILVERLINK ELECTRIC COUNTER-TOP GRIDDLE - CHROME PLATE - W 300 MM - 2.0 KW

MODEL: GS3/C



Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down. The griddle has a chrome surface which both heats up quicker, and transfers heat to food more efficiently than standard griddles, with less energy loss as well as reduced energy radiation, which keeps the kitchen cooler for staff and reduces pressure on the ventilation system. Perfect for cafes, pubs and restaurants, the griddle is thermostatically controlled to give accurate temperatures during the cooking process for consistent results.

**SILVERLINK 600** 

### PRODUCT OPTIONS AND ACCESSORIES

- CC3 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 300 mm
- CN3 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 300 mm
- SLS3 Lincat Silverlink 600 Free-standing Floor Stand for units W 300 mm
- HC3 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 300 mm - 0.25 kW
- HCL3 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 300 mm - 0.25 kW

### **PRODUCT FEATURES**

- Chrome surface heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system
- Transfers heat to food more efficiently than a standard griddle
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Removable front drainer drawer which also makes for easy cleaning.
  Ideal for busy establishments
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up







# LINCAT SILVERLINK ELECTRIC COUNTER-TOP GRIDDLE - CHROME PLATE - W 300 MM - 2.0 KW

**MODEL:** GS3/C

| WEIGHTS & DIMENSIONS |         |
|----------------------|---------|
| Width                | 300 mil |
| Depth                | 600 mil |
| Height               | 330 mil |
| Weight               | 21.7 kg |

| SHIPPING DETAILS           |                                |
|----------------------------|--------------------------------|
| Ship Width                 | 70 cm                          |
| Ship Depth                 | 40 cm                          |
| Ship Height                | 49.5 cm                        |
| Ship Weight                | 23.87 kg                       |
| Number of Shipment Parcels | 1                              |
| Ship Method                | Small Parcel (FedEx, UPS, DHL) |
| Shipping Package Type      | Pieces                         |
| Shipping Origin Zip Code   | LN6 3QZ, UNITED KINGDOM        |
| Quick Ship Product         | No                             |

## **PRODUCT CERTIFICATIONS**



| ENERGY SPECS              |          |                                      |               |
|---------------------------|----------|--------------------------------------|---------------|
| Primary Energy Type       | Electric | Electrical Plug Type                 | UK 3-Pin Plug |
| Electrical Total Amperage | 8.7 A    | Number of Electrical Plugs           | 1             |
| Electrical Volts          | 230V     | Electrical Connection Type           | Cord and Plug |
| Electrical Total Wattage  | 2000 W   | Number of Electrical Conductor Wires | 1             |
| Electrical Kilowatts      | 2 kW     | Dedicated Circuit Required           | No            |
| Electrical Phase          | 1-Phase  | Electrical Remarks                   | Single        |

| ADDITIONAL SPECIFICATIONS          |                     |                             |                          |
|------------------------------------|---------------------|-----------------------------|--------------------------|
| Construction Materials             | Stainless Steel     | Number of Heating Zones     | 2                        |
| Control Type                       | Rotary Control Knob | Plate Thickness             | 12 mm                    |
| Cooking Area Plate Depth           | 405 mm              | Plate Shape                 | Rectangle                |
| Cooking Area Plate Width           | 262 mm              | Ventless Cooking Technology | No                       |
| Cooking Plate Finish Material Type | Chrome Plated       | Temperature Maximum         | 250 °C                   |
| Lower Platen Surface Type          | Smooth              | Temperature Minimum         | 50 °C                    |
| Number Of Controls                 | 2                   | Thermostat Element Location | <b>Under Plate Mount</b> |

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 09, 2025









**MODEL:** GS3/C


## **BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

## **TECHNICAL DRAWING**







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 09, 2025

