



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- SB4 450 GRIDDLE SPLASHB
- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- CN4 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 450 mm
- SLS4 Lincat Silverlink 600 Free-standing Floor Stand - for units W 450 mm

PRODUCT FEATURES

- 12 mm v machined steel plate providing even heat distribution and an easy to clean surface
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up
- Front mounted control for easy of use during cooking
- Piezo ignition for easy lighting of the burners
- Flame failure device for maximum safety

Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Gas Griddle won't let you down. The hard-wearing 12 mm thick steel plate provides even heat distribution and an easy to clean surface, while the griddle is thermostatically controlled to give accurate temperatures during the cooking process for consistent results. The griddle, perfect for cafes, pubs and restaurants, comes with piezo ignition for easy lighting of the burners.

AIA FILE NUMBER:

ITEM NUMBER:



LINCAT SILVERLINK NATURAL GAS COUNTER-TOP GRIDDLE - STEEL PLATE - W 450 MM - 5.4 KW

MODEL: GS4/N

WEIGHTS & DIMENSIONS

Width	450 mil
Depth	650 mil
Height	415 mil
Weight	35.1 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	55 cm
Ship Height	63.5 cm
Ship Weight	38.61 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Gas	Gas Total BTUs	18425 BTU
Electrical Kilowatts	5.4 kW	Gas Inlet Size	0.5 in
Electrical Plug Type	Not Applicable	Gas Inlet Pressure Required	16 mBar
Number of Electrical Plugs	Not Applicable	Gas Consumption at Max Use Per Hour	0.51 m ³
Electrical Connection Type	Not Applicable	Total Heat Input at Max Use	5.4 kW, 16700 BTU per hour
Gas Type	Natural Gas		

ADDITIONAL SPECIFICATIONS

Construction Materials	Stainless Steel	Number of Burners	2
Control Type	Mechanical	Number Of Controls	2
Cooking Area Plate Depth	405 mm	Plate Thickness	12 mm
Cooking Area Plate Width	412 mm	Plate Shape	Rectangle
Cooking Plate Finish Material Type	Polished Steel	Ventless Cooking Technology	No
Lower Platen Surface Type	Smooth	Thermostat Element Location	Under Plate Mount

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

