



SILVERLINK 600

Deliver perfectly crisp on the outside and fluffy on the inside chips time after time with the Silverlink 600 Free Standing Gas Fryer. Twin tanks and twin baskets means you have the flexibility to cook different foods or loads simultaneously, while delivering 46kg of chips an hour. Ideal for cafes, pubs and restaurants, the fryer features piezo ignition for easy lighting and heavy duty nickel plated baskets for the most demanding of operations. You're in control via the accurate thermostat throughout the entire cooking process. Then there's the innovative deep cool zone, which collects cooking debris to prolong the life of the oil and therefore save you money.

A/A FILE NUMBER:

ITEM NUMBER:

PRODUCT FEATURES

- Double tank twin basket operation giving you the flexibility to cook different foods or loads simultaneously, delivering 46kg of chips an hour
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Flame failure device and top temperature cut out ensures safe operation.
- Cool zone collects cooking debris - gives cleaner cooking results and saves money by prolonging the life of the oil
- Piezo ignition for easy lighting
- Heavy duty nickel plated baskets for the most demanding of operations
- Internal drain off tap for easy removal of cooking oil



LINCAT SILVERLINK NATURAL GAS FREE-STANDING TWIN TANK FRYER - 2 BASKETS - W 600 MM - 24.0 KW

MODEL: J10/N

WEIGHTS & DIMENSIONS

| | |
|--------|----------|
| Width | 600 mil |
| Depth | 690 mil |
| Height | 1060 mil |
| Weight | 73.7 kg |

SHIPPING DETAILS

| | |
|----------------------------|-------------------------|
| Ship Width | 81.3 cm |
| Ship Depth | 68.5 cm |
| Ship Height | 122 cm |
| Ship Weight | 81.07 kg |
| Number of Shipment Parcels | 1 |
| Ship Method | LTL Common Carrier |
| Shipping Package Type | Pieces |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product | No |

PRODUCT CERTIFICATIONS



ENERGY SPECS

| | | | |
|----------------------------|------------------|-------------------------------------|------------------------------|
| Primary Energy Type | Gas | Gas Total BTUs | 81880 BTU |
| Electrical Kilowatts | 24 kW | Gas Inlet Size | 0.5 in |
| Electrical Plug Type | Not Applicable | Gas Inlet Pressure Required | 16.3 mBar |
| Number of Electrical Plugs | Not Applicable | Gas Consumption at Max Use Per Hour | 2.29 m ³ |
| Electrical Connection Type | Direct Hardwired | Total Heat Input at Max Use | 22.79 kW, 74000 BTU per hour |
| Gas Type | Natural Gas | | |

ADDITIONAL SPECIFICATIONS

| | | | |
|------------------------|--|-----------------------------|------------|
| Auto Oil Top-Off | No | Number of Burners | 4 |
| Basket Lift Type | Not Applicable | Number of Vats (batteries) | 2 |
| Construction Materials | Stainless Steel | Total Oil Capacity (volume) | 24 l |
| Control Type | Mechanical | Oil Reclamation | No |
| Food Production Rate | 36kg chips -12mm [frozen], 46kg chips -12mm [chilled] per hour | Oil Temperature Control | Mechanical |
| Fryer Type | Open Pot | Pumped Oil Filtration | No |
| Integrated Filtration | No | Vat 1 Oil Capacity (volume) | 12 l |
| Number of Baskets | 2 | Vat 2 Oil Capacity (volume) | 12 l |
| | | Ventless Cooking Technology | No |
| | | Split Pot | Yes |
| | | Temperature Maximum | 190 °C |

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
January 09, 2025

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

