



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE

PRODUCT FEATURES

- Single tank fryer delivering 22.5kg of chips an hour, perfect for pubs, restaurants and care homes
- Front mounted controls for safety
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Flame failure device and top temperature cut out ensures safe operation.
- Cool zone collects cooking debris - gives cleaner cooking results and saves money by prolonging the life of the oil
- Piezo ignition for easy lighting
- Heavy duty nickel plated baskets for the most demanding of operations
- Internal drain off tap for easy removal of cooking oil

Deliver perfectly crisp on the outside and fluffy on the inside chips time after time with the Silverlink 600 Free Standing Gas Fryer. The single tank is capable of delivering 22.5kg of chips an hour. Ideal for pubs, restaurants and care homes, the fryer features piezo ignition for easy lighting and heavy duty nickel plated baskets for the most demanding of operations. You're in control via the accurate thermostat throughout the entire cooking process. Then there's the innovative deep cool zone, which collects cooking debris to prolong the life of the oil and therefore save you money.

A/A FILE NUMBER:

ITEM NUMBER:



LINCAT SILVERLINK NATURAL GAS FREE-STANDING SINGLE TANK FRYER - 1 BASKET - W 300 MM - 12.0 KW

MODEL: J5/N

WEIGHTS & DIMENSIONS

Width	300 mil
Depth	690 mil
Height	1060 mil
Weight	43 kg

SHIPPING DETAILS

Ship Width	85 cm
Ship Depth	45 cm
Ship Height	122 cm
Ship Weight	47.3 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Gas	Gas Total BTUs	40944 BTU
Electrical Kilowatts	12 kW	Gas Inlet Size	0.5 in
Electrical Plug Type	Not Applicable	Gas Inlet Pressure Required	16.3 mBar
Number of Electrical Plugs	Not Applicable	Gas Consumption at Max Use Per Hour	1.14 m ³
Electrical Connection Type	Direct Hardwired	Total Heat Input at Max Use	11.5 kW, 38900 BTU per hour
Gas Type	Natural Gas		

ADDITIONAL SPECIFICATIONS

Auto Oil Top-Off	No	Number of Burners	2
Basket Lift Type	Not Applicable	Number of Vats (batteries)	1
Construction Materials	Stainless Steel	Total Oil Capacity (volume)	12 l
Control Type	Mechanical	Oil Reclamation	No
	18kg chips -12mm	Oil Temperature Control	Mechanical
Food Production Rate	[frozen], 22.5kg chips - 12mm [chilled] per hour	Pumped Oil Filtration	No
Fryer Type	Open Pot	Vat 1 Oil Capacity (volume)	12 l
Integrated Filtration	No	Ventless Cooking Technology	No
Number of Baskets	1	Split Pot	No
		Temperature Maximum	190 °C

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
January 09, 2025

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

