



SILVERLINK 600

#### PRODUCT OPTIONS AND ACCESSORIES

- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE

Deliver perfectly crisp on the outside and fluffy on the inside chips time after time with the Silverlink 600 Free Standing Gas Fryer. The single tank is capable of delivering 22.5kg of chips an hour. Ideal for pubs, restaurants and care homes, the fryer features piezo ignition for easy lighting and heavy duty nickel plated baskets for the most demanding of operations. You're in control via the accurate thermostat throughout the entire cooking process. Then there's the innovative deep cool zone, which collects cooking debris to prolong the life of the oil and therefore save you money.

#### PRODUCT FEATURES

- Single tank fryer delivering 22.5kg of chips an hour, perfect for pubs, restaurants and care homes
- Front mounted controls for safety
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Flame failure device and top temperature cut out ensures safe operation.
- Cool zone collects cooking debris - gives cleaner cooking results and saves money by prolonging the life of the oil
- Piezo ignition for easy lighting
- Heavy duty nickel plated baskets for the most demanding of operations
- Internal drain off tap for easy removal of cooking oil



# LINCAT SILVERLINK PROPANE GAS FREE-STANDING SINGLE TANK FRYER - 1 BASKET - W 300 MM - 12.0 KW

## MODEL: J5/P

### WEIGHTS & DIMENSIONS

Width	300 mil
Depth	690 mil
Height	1060 mil
Weight	43 kg

### SHIPPING DETAILS

Ship Width	85 cm
Ship Depth	45 cm
Ship Height	122 cm
Ship Weight	47.3 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

### PRODUCT CERTIFICATIONS



### ENERGY SPECS

Primary Energy Type	Gas	Gas Total BTUs	38555 BTU
Electrical Kilowatts	11.3 kW	Gas Inlet Size	0.5 in
Electrical Plug Type	Not Applicable	Gas Inlet Pressure Required	25 mBar
Number of Electrical Plugs	Not Applicable	Gas Consumption at Max Use Per Hour	0.81 m <sup>3</sup>
Electrical Connection Type	Direct Hardwired	Total Heat Input at Max Use	11.3 kW, 36800 BTU per hour
Gas Type	Propane		

### ADDITIONAL SPECIFICATIONS

Auto Oil Top-Off	No	Number of Burners	2
Basket Lift Type	Not Applicable	Number of Vats (batteries)	1
Construction Materials	Stainless Steel	Total Oil Capacity (volume)	12 l
Control Type	Mechanical	Oil Reclamation	No
Food Production Rate	18kg chips -12mm [frozen], 22.5kg chips -12mm [chilled] per hour	Oil Temperature Control	Mechanical
Fryer Type	Open Pot	Pumped Oil Filtration	No
Integrated Filtration	No	Vat 1 Oil Capacity (volume)	12 l
Number of Baskets	1	Ventless Cooking Technology	No
		Split Pot	No
		Temperature Maximum	190 °C

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated  
January 09, 2025

**BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

**TECHNICAL DRAWING**

