



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- SLR6/SB - Splashback

PRODUCT FEATURES

- Four powerful gas burners with flame failure device for added safety
- High power gas oven
- Fully pressed and sealed hob tops for easy cleaning
- Robust, easy-to-clean vitreous enamelled cast iron pan supports
- Low level flue maximises working area and enables you to use large stock pots
- Four shelf positions with two removable shelves

Cook a variety of delicious dishes with the powerful Silverlink 600 Gas Oven Range. The four gas burners not only offer power, but also come with a flame failure device for added safety. The oven range, perfect for cafe bars, care homes and small restaurants, has a high power gas oven, and also comes with a low level flue which maximises the working area and enables you to use large stock pots. The fully pressed and sealed hob tops make for easy cleaning, and there are four shelf positions with two removable shelves.



LINCAT SILVERLINK 600 NATURAL GAS FREE-STANDING OVEN RANGE - LEGS AT REAR - 4 BURNERS - W 600 MM - 23.8 KW

MODEL: SLR6C/N

WEIGHTS & DIMENSIONS

Width	485 mm
Depth	600 mm
Height	956 mm
Weight	67.9 kg

SHIPPING DETAILS

Ship Width	81.3 cm
Ship Depth	68.5 cm
Ship Height	110 cm
Ship Weight	74.69 lb
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Gas	Gas Total BTUs	81206 BTU
Electrical Kilowatts	23.8 kW	Gas Inlet Size	0.5 in
Electrical Plug Type	Not Applicable	Gas Inlet Pressure Required	20 mBar
Number of Electrical Plugs	Not Applicable	Gas Consumption at Max Use Per Hour	2.27 m ³
Electrical Connection Type	Not Applicable	Total Heat Input at Max Use	23.8 kW, 81209 BTU per hour
Gas Type	Natural Gas		

ADDITIONAL SPECIFICATIONS

Construction Materials	Stainless Steel	Open or Sealed Burners	Sealed
Control Type	Mechanical, Rotary Control Knob	Oven Power Rating	5.8 kW
Exterior Trim Finish Color	Stainless Steel	Oven Temperature Minimum	130 °C
High Altitude Kit Available	No	Oven Temperature Maximum	250 °C
Number of Heating Zones	4	Shelf Depth	342 mm
Number of Hot Top Burners	4	Shelf Width	480 mm
Number of Shelf Positions	4	Ventless Cooking Technology	No
Number of Shelves	2	Cooking Equipment	Sealed Burner
		BTUs Per Burner	4.5 KW

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
January 09, 2025



**LINCAT SILVERLINK 600 NATURAL GAS FREE-STANDING OVEN
RANGE - LEGS AT REAR - 4 BURNERS - W 600 MM - 23.8 KW**

MODEL: SLR6C/N

SELECT COOKING EQUIPMENT	NUMBER OF	POWER RATING	ARRANGE- MENT	WIDTH	DEPTH
Sealed Burner 1	4	5.8	Center	300 mm	300 mm

SELECT BASE EQUIPMENT	NUMBER OF	CUBIC CAPACITY EACH	WIDTH	DEPTH	HEIGHT
Standard Oven 1	1		485 mm	342 mm	400 mm

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.



TECHNICAL DRAWING

