



For use with multiple electric appliances up to 1000mm wide, the Refresh Midi is ideal for locations where venting to the atmosphere would be impossible, difficult or costly. It provides a safer, more comfortable and productive working environment.

Refresh is a free-standing unit which can be installed quickly and easily, with minimal disruption. It comprises an extract housing, along with a top-mounted filtration section that houses a powerful, efficient fan unit. Air is drawn through the low level filter housing before passing through four filtration stages to remove grease, fine particles, smoke and odours.

PRODUCT OPTIONS AND ACCESSORIES

- SE100/110 Baffle Filter for Refresh Midi Recirculation Unit
- SE100/104 Carbon Filter for Refresh Midi Recirculation Unit
- SE100/101 Filter Set [G4] for Refresh Midi Recirculation Unit
- SE100/107 HEPA Filter for Refresh Midi Recirculation Unit

PRODUCT FEATURES

- Designed for use where venting to the atmosphere is restricted or costly.
- Quick and easy to install.
- Four-stage filtration process removes grease, fine particles, smoke and odours.
- For use with electrical appliances.
- Designed to accommodate multiple pieces of equipment up to 1000mm wide.
- 3 pin commando plug allows users to simply plug in and switch on.
- Delivered in two sections for ease of handling and access.
- Filters need to be cleaned or replaced on a regular basis.

WEIGHTS & DIMENSIONS

Width	1050 mil
Depth	734 mil
Height	2222 mil
Weight	148.5 kg

SHIPPING DETAILS

Ship Width	120 cm
Ship Depth	80 cm
Ship Height	131 cm
Ship Weight	163.35 lb
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	0.68	Electrical Connection Type	Cord and Plug
Electrical Voltage	220/240 volts	Number of Electrical Plugs	1
Electrical Watts	190	Dedicated Circuit Required	Yes
Electrical Phase	Single	Energy Saving	No
Kilowatts	0.19 kW		

ADDITIONAL SPECIFICATIONS

Air Movement CFM	0.26 cm ³ /s
Control Type	On/Off, Rotary Control Knob
Fire Suppression System	No
Hood Type	Canopy
Ventilation Hood Type Rating	Not Applicable

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

