



SILVERLINK 600

#### PRODUCT OPTIONS AND ACCESSORIES

- PSH4 - Pedestal Shelf

#### PRODUCT FEATURES

- Designed to suite with the Silverlink 600 range
- Features an on/off switch and thermostatic control, making them ideal as plate warmers
- Silverlink 600 counter-top units are securely attached to pedestals by means of fixing screws supplied
- Adjustable shelf provides flexibility for storing bulky items
- Adjustable legs for perfect alignment even on uneven floors

Designed to suite with other products in the Silverlink 600 range, the Heated Pedestal features an on/off switch and thermostatic control, making it ideal as a plate warmer.

AIA FILE NUMBER:

ITEM NUMBER:

**WEIGHTS & DIMENSIONS**

Width	450 mm
Depth	600 mm
Height	660 mm
Weight	20.2 kg

**SHIPPING DETAILS**

Ship Width	71.5 cm
Ship Depth	53 cm
Ship Height	74.5 cm
Ship Weight	22.22 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

**WATER, PLUMBING, AND DRAINAGE SPECS**

Water Line Required	No
Drain Line Required	No

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

Primary Energy Type	Electric
Electrical Total Amperage	2.2 A
Electrical Volts	230V
Electrical Total Wattage	500 W
Electrical Kilowatts	0.5 kW
Electrical Phase	1-Phase

Electrical Plug Type	UK 3-Pin Plug
Number of Electrical Plugs	1
Electrical Connection Type	Cord and Plug
Number of Electrical Conductor Wires	1
Dedicated Circuit Required	No
Electrical Remarks	Single

**ADDITIONAL SPECIFICATIONS**

Cabinet Size	Undercounter Height
Construction Materials	Stainless Steel
Control Type	Mechanical, On/Off
Heating System	Electric
Humidity Generation	No
Insulated	No
Internal Depth	567 mm
Internal Height	456 mm

Internal Width	448 mm
Number of Shelf Positions	3
Number of Shelves	1
Shelf Depth	530 mm
Shelf Width	400 mm
Style	Enclosed Cabinet
Temperature Maximum	70 °C
Temperature Minimum	70 °C



LINCAT SILVERLINK FREE-STANDING HEATED OPEN-TOP  
PEDESTAL WITH DOORS - W 450 MM - 0.5 KW

**MODEL: HC4**

**BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

