



Lincat CombiSlim

Measuring just 513mm wide and accommodating 10 full size 1/1 gastronorm, the oven is perfect for front of house and compact kitchens where space is limited but high output and consistent results are needed or for satellite kitchens in combination with our Invoq ovens.

AIA FILE NUMBER:

PRODUCT FEATURES

- CombiSlim provides maximum flexibility in minimum space
- 513mm wide footprint
- Accommodates 10 1/1GN trays
- Consistent regardless of the operator
- Steam injection
- SmartChef® pre-set recipes
- Easy to use SmartTouch®, intuitive touch control display
- CombiSmart® 10 steps, humidity control
- Temperature Probe
- HACCP monitoring
- Available with a Hoodini ventless hood

ITEM NUMBER:

WEIGHTS & DIMENSIONS

Depth	811 mm
Height	948 mm
Weight	81 kg
Clearance Required: Right Side	50 mm

SHIPPING DETAILS

Ship Width	60 cm
Ship Depth	95 cm
Ship Height	110 cm
Ship Weight	95 kg
Number of Shipment Parcels	1
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UK
Quick Ship Product	No

WATER, PLUMBING, AND DRAINAGE SPECS

Water Line Required	Yes
Water Connection Source Type	Plumbed Water Line
Water Inlet Size	0.75 in
Water Inlet Pressure Minimum	2.5 Bar
Water Inlet Pressure Maximum	6 Bar
Drain Line Required	Yes
Drain Location	Underneath
Drain Outlet Size	40 mil

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	Hardwired
Electrical Amps Per Conductor	L1=21; L2=21; L3=21	Number of Electrical Plugs	Not Applicable
Electrical Total Amperage	63 A	Electrical Connection Type	Direct Hardwired
Electrical Volts	400V	Number of Electrical Conductor Wires	1
Electrical Total Wattage	12700 W	Dedicated Circuit Required	Yes
Electrical Kilowatts	12.7 kW	Electrical Remarks	Three
Electrical Hertz	50 Hz	Steam Source	Direct Steam
Electrical Phase	3-Phase		

ADDITIONAL SPECIFICATIONS

Boiler Based or Boilerless	Boilerless	Instant Steam On Demand	Yes
Construction Materials	Stainless Steel	Interior	Stainless Steel
Control Type	7" Touch Screen (VS7)	Manual Or Automatic Cooling	Manual Cooling
Cooking Chamber Depth	629 mm	Number Of Cooking Chambers	1
Cooking Chamber Height	551 mm	Passthrough	No
Cooking Chamber Width	402 mm	Ventless Cooking Technology	No
Door Hinge Type	Field Reversible, Left Hang Hinge	Temperature Maximum	300 °C
Full-Size Or Half-Size	Half-Size	Temperature Minimum	30 °C
		Timed Steam Injection	Yes

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

