



**SILVERLINK 600**

#### PRODUCT OPTIONS AND ACCESSORIES

- ABP03 Branding Plate Kit
- SGE1/BS Bench Stand
- SGE1/WS Wall Stand
- SGE1/FS Floor Stand
- BR15 Wall Bracket

#### PRODUCT FEATURES

- The performance of a Lincat GR3 while delivering a 50% energy saving
- On-demand cooking delivers savings without operational compromise
- Sleep mode to achieve maximum energy savings during quieter periods
- Customisable full power and 50% timers to tailor the grill to your menu and the desired level of energy saving
- 50% power mode keeps the cavity warm for fast recovery
- High-temperature glass covered elements and removable roasting rack and crumb tray, make it effortless to keep clean
- 4 shelf positions to give maximum flexibility for all catering operations
- Plug and play - UK 3 Pin Plug

AIA FILE NUMBER:

ITEM NUMBER:

#### WEIGHTS & DIMENSIONS

Width	635 mm
Depth	373 mm
Height	347 mm
Weight	25.9 kg
Clearance Required: Top	500 mm
Clearance Required: Front	1000 mm
Clearance Required: Left Side	300 mm
Clearance Required: Right Side	300 mm

#### SHIPPING DETAILS

Ship Width	55 cm
Ship Depth	70 cm
Ship Height	49.6 cm
Ship Weight	29 kg
Number of Shipment Parcels	1
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

#### PRODUCT CERTIFICATIONS



#### ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	UK 3-Pin Plug
Electrical Total Amperage	12.2 A	Number of Electrical Plugs	1
Electrical Volts	230V	Electrical Connection Type	Cord and Plug
Electrical Total Wattage	2800 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	2.8 kW	Dedicated Circuit Required	Yes
Electrical Phase	1-Phase	Electrical Remarks	Single

#### ADDITIONAL SPECIFICATIONS

Broiler Base Configuration	Not Applicable	Heat Location	Top Only
Broiler Type	Salamander	Heat Source Type	Infrared
Construction Materials	Stainless Steel	Number of Heating Zones	1
Control Type	Electronic, Push Button	Number of Shelf Positions	4
Cooking Area Plate Depth	230 mm	Ventless Cooking Technology	No
Cooking Area Plate Width	410 mm		

#### BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

