



SGD-120LGE

High-end Backbar Cooler

Product Features

- Suitable for bottles and KEGS
- Left hinged glass door
- Low energy consumption
- Adjustable plate shelves
- LED interior light with switch
- Adjustable legs
- Skinplate exterior/interior
- Digital controller and temperature display
- Automatic defrost
- Easy maintenance condenser
- Lock

Spacious backbar cooler with left-hinged glass door

The SGD glass door version is built to deliver exceptional style and product presentation combined with superior energy efficiency. This premium cabinet works well for displaying cans and bottles of different shapes and sizes, as the adjustable plate shelves provide a stable, practical surface for easy organization.

Designed with hospitality in mind, the SGD features a sleek anthracite exterior that blends effortlessly into modern, high-end settings. Its coated skinplate interior and exterior are resistant to scratches and visible fingerprints, ensuring it stays looking great even with daily use.

The energy-efficient cooling system ensures a consistent temperature while keeping running costs under control. The temperature can be set easily on the electronic controller and it has automatic defrost for easy maintenance.

Measures and Content

Temperature Range	°C	+2 to +10
Climate Class		4
Gross / Net Weight	kg	63 / 58
Gross Volume	l	135
Net Volume	l	124
Gross / Net Volume	l	135 / 124

Design and Material

Bottom Shelf Dimensions		488 x 275
Door Number & Type		1 hinged glass door
Max load on Shelves	kg/m ²	165
No. of Doors		1
No. of Shelves	pcs	2
Shelf Color		Silver
Shelf Dimensions		470 x 355 mm
Shelves Number & Type		2 adjustable
Tempered glass		No
Feet / Legs		Adjustable Feet
Exterior Finish		Anthracite RAL 7021
Interior Finish		Silver
Interior Light		LED
Lock		Yes

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	60
Thermometer		Yes

Power and Consumption

Energy Class		D
Energy Consumption	kWh/24h	1.21
Annual Energy Consumption	kWh/year	443
EEl	%	40
Input Power	W	327
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	47

Dimensions

Internal Dimension (WxDxH)	mm	488 x 425 x 682
External Dimension (WxDxH)	mm	555 x 640 x 850
Packed Dimension (WxDxH)	mm	980 x 640 x 580 mm
40ft Container Load	pcs	152



Adjustable shelves



Digital controller