



## SPID250

Serve Over Counter

### Product Features

- Excellent product visibility
- Glass structure for protection of food
- Front glass hinges forward if required
- Accepts GN1/1 pan(s) (not supplied)
- Easy access understorage
- Black exterior
- Ventilated cooling
- Automatic defrost
- LED interior light

Ventilated serve over display counter

The SPID serve over counter offers the ultimate cooling solution for your food display needs. A visual and functional delight, it's perfect for sandwich shops, delis, and supermarkets to exhibit their offerings enticingly. It has a flat glass canopy for good hygiene and the front glass hinges forward for easy cleaning. The serve over counter is suitable for gastronorm pans (not included). The contemporary counter has an effective ventilated cooling system, which circulates cool air evenly throughout the cabinet. It is designed to keep your products at the ideal temperature while offering easy access.

### Measures and Content

|                    |     |           |
|--------------------|-----|-----------|
| Gross / Net Weight | kg  | 297 / 277 |
| Capacity GN Pans   | pcs | 6 x GN1/1 |
| Gross / Net Volume | l   | /         |
| Total Display Area | m²  | 1.9       |
| Temperature Range  | °C  | -1 to +5  |
| Climate Class      |     | 3         |

### Design and Material

|                 |                   |
|-----------------|-------------------|
| Exterior Finish | Black RAL9005     |
| Interior Finish | White RAL9003     |
| Feet / Legs     | 6 adjustable feet |
| Interior Light  | Yes               |

### Cooling and Functions

|                    |            |
|--------------------|------------|
| Type of Controller | Electronic |
| Type of Cooling    | Ventilated |
| Type of Defrost    | Automatic  |
| Refrigerant        | R290       |
| Refrigerant Charge | g150       |
| Thermometer        | Yes        |

### Power and Consumption

|                           |          |            |
|---------------------------|----------|------------|
| Energy Consumption        | kWh/24h  | 13.7       |
| Annual Energy Consumption | kWh/year | 5001       |
| Input Power               | W        | 1284       |
| Voltage / Frequency       | V/Hz     | 220-240/50 |
| Noise Level               | dB(A)    | 56         |

### Dimensions

|                            |     |                    |
|----------------------------|-----|--------------------|
| External Dimension (WxDxH) | mm  | 2465 x 960 x 1235  |
| Internal Dimension (WxDxH) | mm  | 2396 x 670         |
| Packed Dimension (WxDxH)   | mm  | 2625 x 1065 x 1230 |
| 40ft Container Load        | pcs | 16                 |



Designed for GN1/1 pans,  
not supplied



Thermometer