Blizzard™

PRODUCT SPECIFICATION SHEET

Product	**LUXE6** 6 Pan Ice Cream Serve Over
Warranty	3 Year Warranty

COMPLIANCE	
County of Manufacture	China
GTIN	5060486685523
Commodity Code	8419818090
UKCA	Yes
CE	Yes

DELIVERY	
Special Order Unit	No
Modified Unit	No
Delivery Group	T1-G3
Default Carrier	9 - Hadfields
Next Day Delivery	No

PACKAGING & SHIPPING			
Packaging Height (mm)	1495	Waste Cardboard Packaging (KG)	N/A
Packaging Width (mm)	1020	Waste Plastic Packaging (KG)	1.5
Packaging Depth (mm)	990	Waste Wood Packaging (KG)	18.5

MEASUREMENTS & CAPACITY			
External Unit Height (mm)	1300	Net Weight (kg)	170
External Unit Width (mm)	910	Gross Weight (kg)	200
External Unit Depth (mm)	880	Net Capacity (L)	30
Internal Unit Height (mm)	725	Gross Capacity (L)	189
Internal Unit Width (mm)	465	Display Capacity (M^2)	0.41
Internal Unit Depth (mm)	515		

TEMPERATURE	
Temperature Range	-16°C ~ -18°C
Max Ambient Temperature	30°C
Climate Class	4

PLUMBING & WATER	
Water Required	No
Water Usage (L)	N/A
Drainage Required	No

Blizzard™

PRODUCT SPECIFICATION SHEET

ELECTRICAL & ENERGY			
Power Supply	13amp	KWH Annum	4651
Power Consumption (W)	860	EEI	28.6
Rated Current (A)	4.3	Storage Energy Rating	N/A
KWH Per 24/hr	12.74	Display Energy Rating	C

FURTHER DETAILS			
Finish	Black	Cooling	Ventilated
Alternative Finish	Silver	Refrigerant	R290
Material	Coated Steel	Refrigerant Amount (g)	148
Internal Material	Stainless Steel	Defrost	Automatic
Number Of Doors	2	Noise Level (db)	66
Door Type	Sliding	Production 24/hr	N/A
Number Of Drawers	N/A	Ice Type	N/A
Nightblind	No	Ice Size (mm)	N/A
Shelves Supplied	N/A	Bin Capacity (kg)	N/A
Shelf Width (mm)	N/A	Requires Construction	No
Shelf Depth (mm)	N/A	Slot Size (mm)	N/A
Deck Size	W840 x D900	Grill Size (mm)	N/A
Basket Capacity	N/A	Bottle Capacity	N/A
Basket Supplied	N/A	Glass Capacity	N/A
Basket Size	N/A	Dish Capacity	N/A
Container Capacity	6 x 5L Napoli Pan	Baskets Per Hour	N/A
Containers Supplied	6 x 5L Napoli Pan	Keg Capacity	N/A
Controller	Digital Controller	Bowl Capacity	N/A
Controller Type	RTEC-TK-07	ETL Accredited	No